

LSA 44.3

Low Voltage Alternator - 4 pole

70 to 200 kVA - 50 Hz / 88 to 250 kVA - 60 Hz
Electrical and mechanical data

LEROY-SOMER™

Nidec
All for dreams

Specially adapted to applications

The LSA 44.3 alternator is designed to be suitable for typical generator applications, such as: backup, prime power, cogeneration, marine applications, rental, telecommunications, etc.

Compliant with international standards

The LSA 44.3 alternator conforms to the main international standards and regulations: IEC 60034, NEMA MG 1.32-33, ISO 8528-3, CSA C22.2 n°100-14, UL 1446 (UL 1004 on request), marine regulations, etc.
It can be integrated into a EC marked generator.
The LSA 44.3 is designed, manufactured and marketed in an ISO 9001 environment and ISO 14001.

Top of the range electrical performance

- Class H insulation
- Standard 12 wire re-connectable winding, 2/3 pitch, type no. 6
- Voltage range:
  - 50 Hz: 220 V - 240 V and 380 V - 415 V (440 V)
  - 60 Hz: 208 V - 240 V and 380 V - 480 V
- High efficiency and motor starting capacity
- Other voltages are possible with optional adapted windings:
  - 50 Hz: 440 V (no. 7), 500 V (no. 9), 690 V (n°10 or 52)
  - 60 Hz: 380 V and 416 V (no. 8), 600 V (no. 9)
- Complies with EN 61000-6-3, EN 61000-6-2, EN 55011, group 1 class B for European zone (EC marking)

Reinforced mechanical structure using finite element modelling

- Compact rigid assembly to better withstand generator vibrations
- Steel frame and terminal box
- Aluminium/cast iron flanges and shields
- Two-bearing and single-bearing versions designed to be suitable for commercially-available heat engines
- Half-key balancing two bearing
- Permanently greased bearings (20 000h)
- Direction of rotation: clockwise and anti-clockwise (without derating)

Excitation and regulation system suited to the application

Excitation system				Regulation options			
Voltage regulator	**SHUNT**	**AREP** (option)	**PMG** (option)	**C.T.** Current transformer for paralleling	Mains paralleling	3-phase sensing	Remote voltage potentiometer
R250	**Standard**	**-**	**-**	**-**	**-**	**-**	√
D350	**-**	**Standard**	**Standard**	√	**-**	√	√
D550	**Option**	**Option**	**Option**	√	√	√	√

√ : Possible option

Compact and design terminal box

- Easy access to the AVR (lid) and to the connections
- Terminal block for reconnecting the voltage

Protection system suited to the environment

- The LSA 44.3 is IP 23
- Standard winding protection for clean environments with relative humidity ≤ 95%, including indoor marine environments
- Options:
  - Filters on air inlet: derating 5%
  - Filters on air inlet and air outlet (IP 44) : derating 10%
  - Space heaters
  - Thermal protection for stator windings
  - Winding protection for harsh environments and relative humidity greater than 95%
  - Shaft height: H = 225 mm on demand
  - Cable outlet at right



General characteristics

Insulation class	H
Winding pitch	2/3 (wdg 6)
Number of wires	12
Protection	IP 23
Altitude	≤ 1000 m
Overspeed	2250 min^{-1}
Air flow	0.25m^3/s, 50 Hz - 0.30m^3/s, 60 Hz
Air flow (***)	0.29m^3/s, 50 Hz - 0.34m^3/s, 60 Hz

(***) Only for LS 44.3 L12, VL13 & VL14

Excitation system	SHUNT	AREP / PMG
AVR type	R250	D350
Voltage regulation (*)	± 0.5%	± 0.25%
Short-circuit current	-	300% (3 IN): 10 s
Total Harmonic Distortion THD (**) in no-load .....:	< 2%	
Total Harmonic Distortion THD (**) on linear load ..:	< 5%	
Waveform: NEMA = TIF (**)	< 50	

(*) Steady state. (**) Total harmonic distortion between phases, no-load or on-load (non-distorting).

Ratings 50 Hz - 1500 R.P.M.

kVA / kW * - P.F. = 0.8

Duty/T°C		Continuous duty/40°C					Continuous duty/40°C					Stand-by/40°C					Stand-by/27°C				
Class/T°K		H/125°K					F/105°K					H/150°K					H/163°K				
Phase		3 ph.				1 ph.	3 ph.				1 ph.	3 ph.				1 ph.	3 ph.				1 ph.
Y		380V	400V	415V	440V	ΔΔ	380V	400V	415V	440V	ΔΔ	380V	400V	415V	440V	ΔΔ	380V	400V	415V	440V	ΔΔ
Δ		220V	230V	240V		230V	220V	230V	240V		230V	220V	230V	240V		230V	220V	230V	240V		230V
YY					220V					220V					220V					220V	
LSA 44.3 S2	kVA	70	**70**	70	63	42	64	**64**	64	57	38	74	**74**	74	67	45	77	**77**	77	69	46
	kW	*56*	*56*	*56*	*50*	*33.5*	*51*	*51*	*51*	*46*	*30.5*	*59*	*59*	*59*	*54*	*36*	*62*	*62*	*62*	*55*	*37*
LSA 44.3 S3	kVA	80	**80**	80	72	48	73	**73**	73	66	44	85	**85**	85	76	51	88	**88**	88	79	53
	kW	*64*	*64*	*64*	*58*	*38.5*	*58*	*58*	*58*	*53*	*35*	*68*	*68*	*68*	*61*	*41*	*70*	*70*	*70*	*63*	*42*
LSA 44.3 S4	kVA	90	**90**	90	81	54	82	**82**	82	74	49	95	**95**	95	86	57	100	**100**	100	89	59
	kW	*72*	*72*	*72*	*65*	*43*	*66*	*66*	*66*	*59*	*39*	*76*	*76*	*76*	*69*	*46*	*80*	*80*	*80*	*71*	*47*
LSA 44.3 S5	kVA	100	**100**	100	90	60	91	**91**	91	82	55	106	**106**	106	95	64	110	**110**	110	99	66
	kW	*80*	*80*	*80*	*72*	*48*	*73*	*73*	*73*	*66*	*44*	*85*	*85*	*85*	*76*	*51*	*88*	*88*	*88*	*79*	*53*
LSA 44.3 M6	kVA	125	**125**	125	113	67	114	**114**	114	103	61	133	**133**	133	120	71	138	**138**	138	124	74
	kW	*100*	*100*	*100*	*90*	*54*	*91*	*91*	*91*	*82*	*49*	*106*	*106*	*106*	*96*	*57*	*110*	*110*	*110*	*99*	*59*
LSA 44.3 M8	kVA	135	**135**	135	122	73	123	**123**	123	111	66	143	**143**	143	129	77	150	**150**	150	134	80
	kW	*108*	*108*	*108*	*98*	*58*	*98*	*98*	*98*	*89*	*53*	*114*	*114*	*114*	*103*	*62*	*120*	*120*	*120*	*107*	*64*
LSA 44.3 L10	kVA	150	**150**	150	135	80	137	**137**	137	123	73	159	**159**	159	143	85	165	**165**	165	149	88
	kW	*120*	*120*	*120*	*108*	*64*	*110*	*110*	*110*	*98*	*58*	*127*	*127*	*127*	*114*	*68*	*132*	*132*	*132*	*119*	*70*
LSA 44.3 L12	kVA	165	**165**	165	138	88	150	**150**	150	126	80	175	**175**	175	150	93	182	**182**	182	157	97
	kW	*132*	*132*	*132*	*110*	*70*	*120*	*120*	*120*	*101*	*64*	*140*	*140*	*140*	*120*	*74*	*146*	*146*	*146*	*126*	*78*
LSA 44.3 VL13	kVA	180	**180**	180	171	90	164	**164**	164	156	82	191	**191**	191	181	95	200	**200**	200	188	99
	kW	*144*	*144*	*144*	*137*	*72*	*131*	*131*	*131*	*125*	*66*	*153*	*153*	*153*	*145*	*76*	*160*	*160*	*160*	*150*	*79*
LSA 44.3 VL14	kVA	192	**200**	200	192	100	175	**182**	182	175	91	204	**212**	212	204	106	211	**220**	220	211	110
	kW	*154*	*160*	*160*	*154*	*80*	*140*	*146*	*146*	*140*	*73*	*163*	*170*	*170*	*163*	*85*	*169*	*176*	*176*	*169*	*88*

Ratings 60 Hz - 1800 R.P.M.

kVA / kW * - P.F. = 0.8

Duty/T°C		Continuous duty/40°C					Continuous duty/40°C					Stand-by/40°C					Stand-by/27°C				
Class/T°K		H/125°K					F/105°K					H/150°K					H/163°K				
Phase		3 ph.				1 ph.	3 ph.				1 ph.	3 ph.				1 ph.	3 ph.				1 ph.
Y		380V	416V	440V	480V	ΔΔ	380V	416V	440V	480V	ΔΔ	380V	416V	440V	480V	ΔΔ	380V	416V	440V	480V	ΔΔ
Δ		220V	240V			240V	220V	240V			240V	220V	240V			240V	220V	240V			240V
YY			208V	220V	240V			208V	220V	240V			208V	220V	240V			208V	220V	240V	
LSA 44.3 S2	kVA	69	76	80	**88**	46	63	69	73	**80**	42	73	81	85	**93**	49	76	84	88	**97**	51
	kW	*55*	*61*	*64*	*70*	*37*	*50*	*55*	*58*	*64*	*33.5*	*58*	*65*	*68*	*74*	*39*	*61*	*67*	*70*	*78*	*41*
LSA 44.3 S3	kVA	79	87	92	**100**	52	72	79	84	**91**	47	84	92	98	**106**	55	87	96	101	**110**	57
	kW	*63*	*70*	*74*	*80*	*42*	*58*	*63*	*67*	*73*	*37.5*	*67*	*74*	*78*	*85*	*44*	*70*	*77*	*81*	*88*	*46*
LSA 44.3 S4	kVA	89	98	103	**113**	59	81	89	94	**103**	54	94	104	109	**120**	63	98	108	113	**124**	65
	kW	*71*	*78*	*82*	*90*	*47*	*65*	*71*	*75*	*82*	*43*	*75*	*83*	*87*	*96*	*50*	*78*	*86*	*90*	*99*	*52*
LSA 44.3 S5	kVA	99	108	115	**125**	65	90	99	105	**114**	59	105	114	122	**133**	69	109	119	127	**138**	72
	kW	*79*	*86*	*92*	*100*	*52*	*72*	*79*	*84*	*91*	*47*	*84*	*91*	*98*	*106*	*55*	*87*	*95*	*102*	*110*	*58*
LSA 44.3 M6	kVA	124	135	143	**156**	76	113	123	130	**142**	69	131	143	152	**165**	81	136	149	157	**172**	84
	kW	*99*	*108*	*114*	*125*	*61*	*90*	*98*	*104*	*114*	*55*	*105*	*114*	*122*	*132*	*65*	*109*	*119*	*126*	*138*	*67*
LSA 44.3 M8	kVA	134	146	155	**169**	81	122	133	141	**154**	74	142	155	164	**179**	86	147	161	171	**186**	89
	kW	*107*	*117*	*124*	*135*	*65*	*98*	*106*	*113*	*123*	*59*	*114*	*124*	*131*	*143*	*69*	*118*	*129*	*137*	*149*	*71*
LSA 44.3 L10	kVA	148	163	172	**188**	95	135	148	157	**171**	86	157	173	182	**199**	101	163	179	189	**207**	105
	kW	*118*	*130*	*138*	*150*	*76*	*108*	*118*	*126*	*137*	*69*	*126*	*138*	*146*	*159*	*81*	*130*	*143*	*151*	*166*	*84*
LSA 44.3 L12	kVA	165	179	189	**206**	105	150	163	172	**187**	96	175	190	200	**218**	111	182	197	208	**227**	116
	kW	*132*	*143*	*151*	*165*	*84*	*120*	*130*	*138*	*150*	*77*	*140*	*152*	*160*	*174*	*89*	*146*	*158*	*166*	*182*	*93*
LSA 44.3 VL13	kVA	180	195	210	**225**	113	164	177	191	**205**	102	191	207	223	**239**	119	200	215	231	**250**	124
	kW	*144*	*156*	*168*	*180*	*90*	*131*	*142*	*153*	*164*	*82*	*153*	*166*	*178*	*191*	*95*	*160*	*172*	*185*	*200*	*99*
LSA 44.3 VL14	kVA	200	215	230	**250**	125	182	196	209	**228**	114	212	228	244	**265**	133	220	237	253	**275**	136
	kW	*160*	*172*	*184*	*200*	*100*	*146*	*157*	*167*	*182*	*91*	*170*	*182*	*195*	*212*	*106*	*176*	*190*	*202*	*220*	*109*

* Values are rounded-off and are subject to change without notice by the manufacturer.

Efficiencies 400 V - 50 Hz (— P.F.: 0.8) (····· P.F.: 1)





















Efficiencies 480 V - 60 Hz (— P.F.: 0.8) (····· P.F.: 1)





















Reactances (%). Time constants (ms) - Class H / 400 V

		S2	S3	S4	S5	M6	M8	L10	L12	VL13	VL14
Kcc	Short-circuit ratio	0.68	0.59	0.61	0.55	0.45	0.44	0.49	0.44	0.37	0.33
Xd	Direct-axis synchro. reactance unsaturated	239	273	258	287	329	323	305	335	343	381
Xq	Quadrature-axis synchro. reactance unsaturated	121	139	131	146	167	165	155	171	175	194
T'do	No-load transient time constant	2308	2308	2211	2211	2154	2112	2077	2077	2025	2025
X'd	Direct-axis transient reactance saturated	10.3	11.8	11.6	12.9	15.2	15.3	14.6	16.1	16.9	18.8
T'd	Short-circuit transient time constant	100	100	100	100	100	100	100	100	100	100
X"d	Direct-axis subtransient reactance saturated	6.2	7	7	7.7	9.1	9.1	8.8	9.6	10.1	11.3
T"d	Subtransient time constant	10	10	10	10	10	10	10	10	10	10
X"q	Quadrature-axis subtransient reactance saturated	13.2	15.1	14.5	16.1	18.6	18.3	17.4	19.1	19.7	21.9
Xo	Zero sequence reactance	0.43	0.49	0.48	0.54	0.63	0.63	0.61	0.67	0.7	0.78
X2	Negative sequence reactance saturated	9.74	11.13	10.75	11.95	13.89	13.78	13.11	14.42	14.96	16.62
Ta	Armature time constant	15	15	15	15	15	15	15	15	15	15

Other class H / 400 V data

io (A)	No-load excitation current SHUNT	0.75	0.75	0.73	0.73	0.66	0.62	0.67	0.67	0.78	0.78
io (A)	No-load excitation current AREP	0.97	0.97	0.94	0.94	0.85	0.81	0.86	0.86	0.78	0.78
ic (A)	On-load excitation current SHUNT	2.07	2.33	2.11	2.31	2.47	2.37	2.45	2.71	3.17	3.53
ic (A)	On-load excitation current AREP	2.67	3	2.71	2.98	3.18	3.05	3.15	3.49	3.17	3.53
uc (V)	On-load excitation voltage SHUNT	23.1	25.8	26.5	28.9	30.6	29.3	29.9	32.7	16.2	17.9
uc (V)	On-load excitation voltage AREP	18.6	20.7	21.3	23.2	24.5	23.5	24	26.3	16.2	17.9
ms	Response time (ΔU = 20% transient)	500	500	500	500	500	500	500	500	500	500
kVA	Start (ΔU = 20% cont. or ΔU = 30% trans.) SHUNT*	184	184	292	293	310	334	371	379	487	487
kVA	Start (ΔU = 20% cont. or ΔU = 30% trans.) AREP*	222	221	344	344	366	400	414	414	545	545
%	Transient ΔU (on-load 4/4) SHUNT - P.F.: 0.8 $_{LAG}$	13.3	14.5	11.6	12.4	13.8	13.8	13.4	14.3	13	13.9
%	Transient ΔU (on-load 4/4) AREP - P.F.: 0.8 $_{LAG}$	11.8	12.9	10.4	11.1	12.3	12.3	12	12.7	11.6	12.4
W	No-load losses	2174	2174	2396	2396	2387	2478	2894	2946	2670	2670
W	Heat dissipation	5025	5892	6073	6935	8254	8251	8914	10236	10165	11933

* P.F. = 0.6

Reactances (%). Time constants (ms) - Class H / 480 V

		S2	S3	S4	S5	M6	M8	L10	L12	VL13	VL14
Kcc	Short-circuit ratio	0.65	0.57	0.58	0.53	0.43	0.42	0.47	0.43	0.36	0.32
Xd	Direct-axis synchro. reactance unsaturated	250	284	270	299	342	337	318	349	358	397
Xq	Quadrature-axis synchro. reactance unsaturated	127	145	137	152	174	172	162	178	182	202
T'do	No-load transient time constant	2308	2308	2211	2211	2154	2112	2077	2077	2025	2025
X'd	Direct-axis transient reactance saturated	10.8	12.3	12.2	13.5	15.8	15.9	15.3	16.8	17.6	19.6
T'd	Short-circuit transient time constant	100	100	100	100	100	100	100	100	100	100
X"d	Direct-axis subtransient reactance saturated	6.5	7.3	7.3	8.1	9.5	9.5	9.2	10	10.6	11.7
T"d	Subtransient time constant	10	10	10	10	10	10	10	10	10	10
X"q	Quadrature-axis subtransient reactance saturated	13.9	15.7	15.1	16.7	19.3	19.1	18.1	19.9	20.5	22.8
Xo	Zero sequence reactance	0.45	0.51	0.5	0.56	0.66	0.66	0.63	0.7	0.73	0.81
X2	Negative sequence reactance saturated	10.2	11.59	11.25	12.44	14.44	14.37	13.7	15	15.59	17.32
Ta	Armature time constant	15	15	15	15	15	15	15	15	15	15

Other class H / 480 V data

io (A)	No-load excitation current SHUNT	0.75	0.75	0.73	0.73	0.66	0.62	0.67	0.67	0.77	0.77
io (A)	No-load excitation current AREP	0.97	0.97	0.94	0.94	0.85	0.81	0.86	0.86	0.77	0.77
ic (A)	On-load excitation current SHUNT	2.08	2.31	2.13	2.32	2.47	2.38	2.44	2.68	3.21	3.56
ic (A)	On-load excitation current AREP	2.67	2.98	2.75	2.99	3.18	3.06	3.14	3.45	3.21	3.56
uc (V)	On-load excitation voltage SHUNT	23.5	26	27	29.4	31	29.7	30.3	33	16.6	18.3
uc (V)	On-load excitation voltage AREP	18.8	20.8	21.7	23.6	24.9	23.9	24.3	26.5	16.6	18.3
ms	Response time (ΔU = 20% transient)	500	500	500	500	500	500	500	500	500	500
kVA	Start (ΔU = 20% cont. or ΔU = 30% trans.) SHUNT*	220	222	352	351	374	403	465	466	589	587
kVA	Start (ΔU = 20% cont. or ΔU = 30% trans.) AREP*	265	265	422	423	446	481	541	544	708	706
%	Transient ΔU (on-load 4/4) SHUNT - P.F.: 0.8 $_{LAG}$	13.7	14.9	12	12.7	14.1	14.2	13.8	14.7	13.3	14.3
%	Transient ΔU (on-load 4/4) AREP - P.F.: 0.8 $_{LAG}$	12.2	13.2	10.7	11.4	12.6	12.6	12.3	13	11.9	12.7
W	No-load losses	3188	3188	3501	3501	3506	3639	4217	4308	3928	3928
W	Heat dissipation	6152	7047	7349	8241	9669	9747	10581	11988	12155	14140

* P.F. = 0.6

Transient voltage variation 400V - 50 Hz



Phase loading (SHUNT) - kVA at P.F. = 0.8



Phase loading (AREP/PMG) - kVA at P.F. = 0.8



Load shedding (SHUNT) - kVA at P.F. = 0.8



Load shedding (AREP/PMG) - kVA at P.F. = 0.8



Motor starting (SHUNT)
Locked rotor kVA at P.F. = 0.6



Motor starting (AREP/PMG)
Locked rotor kVA at P.F. = 0.6

1) For a starting P.F. other than 0.6, the starting kVA must be multiplied by K = Sine P.F. / 0.8
2) For voltages other than 400V (Y), 230V (Δ) at 50 Hz, then kVA must be multiplied by $(400/U)^2$ or $(230/U)^2$.

Transient voltage variation 480V - 60 Hz



Phase loading (SHUNT) - kVA at P.F. = 0.8



Phase loading (AREP/PMG) - kVA at P.F. = 0.8



Load shedding (SHUNT) - kVA at P.F. = 0.8



Load shedding (AREP/PMG) - kVA at P.F. = 0.8



Motor starting (SHUNT)
Locked rotor kVA at P.F. = 0.6



Motor starting (AREP/PMG)
Locked rotor kVA at P.F. = 0.6

1) For a starting P.F. other than 0.6, the starting kVA must be multiplied by K = Sine P.F. / 0.8
2) For voltages other than 480V (Y), 277V (Δ), 240V (YY) at 60 Hz, then kVA must be multiplied by $(480/U)^2$ or $(277/U)^2$ or $(240/U)^2$.

3-phase short-circuit curves at no load and rated speed (star connection Y)

LSA 44.3 S2

Symmetrical ——
Asymmetrical - - -



LSA 44.3 S3

Symmetrical ——
Asymmetrical - - -



LSA 44.3 S4

Symmetrical ——
Asymmetrical - - -



Influence due to connection
Curves shown are for star (Y) connection.
For other connections, use the following multiplication factors:
- Series delta : current value x 1.732 - Parallel star : current value x 2

3-phase short-circuit curves at no load and rated speed (star connection Y)

LSA 44.3 S5

Symmetrical ——
Asymmetrical - - -



LSA 44.3 M6

Symmetrical ——
Asymmetrical - - -



LSA 44.3 M8

Symmetrical ——
Asymmetrical - - -



Influence due to short-circuit
Curves are based on a three-phase short-circuit.
For other types of short-circuit, use the following multiplication factors.

	3-phase	2-phase L/L	1-phase L/N
Instantaneous (max.)	1	0.87	1.3
Continuous	1	1.5	2.2
Maximum duration (AREP/PMG)	10 sec.	5 sec.	2 sec.

3-phase short-circuit curves at no load and rated speed (star connection Y)

LSA 44.3 L10

Symmetrical ——
Asymmetrical - - -



LSA 44.3 L12

Symmetrical ——
Asymmetrical - - -



Influence due to connection
Curves shown are for star (Y) connection.
For other connections, use the following multiplication factors:
- Series delta : current value x 1.732 - Parallel star : current value x 2

3-phase short-circuit curves at no load and rated speed (star connection Y)

LSA 44.3 VL13

Symmetrical ——
Asymmetrical - - -



LSA 44.3 VL14

Symmetrical ——
Asymmetrical - - -



Influence due to short-circuit
Curves are based on a three-phase short-circuit.
For other types of short-circuit, use the following multiplication factors.

	3-phase	2-phase L/L	1-phase L/N
Instantaneous (max.)	1	0.87	1.3
Continuous	1	1.5	2.2
Maximum duration (AREP/PMG)	10 sec.	5 sec.	2 sec.

Single bearing dimensions



Dimensions (mm) and weight				
Type	L without PMG maxi*	LB	Xg	Weight (kg)
LSA 44.3 S2	758	677	313	295
LSA 44.3 S3	758	677	313	295
LSA 44.3 S4	758	677	329	332
LSA 44.3 S5	758	677	329	332
LSA 44.3 M6	828	747	353	368
LSA 44.3 M8	828	747	365	398
LSA 44.3 L10	868	787	383	433
LSA 44.3 L12	868	787	383	433
LSA 44.3 VL13	953	872	416	554
LSA 44.3 VL14	953	872	416	554

* L maxi = LB + AH maxi + 19

Shaft height (mm)			
	Standard	*Option*	
H	**270**	*225**	*280***
	Feet length		
C	405	*332.5*	*429*
A1	406	*356*	*457*
A2	474	*474*	*541*
Z	20	*14.5*	*20*
Z1	25	*20*	*25*
Z2	50	*40*	*50*
W	150	*120*	*150*

* Not available for VL13 and VL14
** Available only for VL13 and VL14

Coupling				
Flange	**1**	**2**	**3**	**4**
Flex plate				
14	x	-	-	-
11 ½	x	x	x	-
10	x	x	x	x
8	-	-	x	x

Flange (mm)					
S.A.E.	P	N	M	S	XBG
4	400	361.95	381	11	12
3	445	409.58	428.62	11	12
2	485	447.68	466.72	11	12
1	560.5*	511.18	530.23	12	10

* VL13 and VL14 = 550 mm

Flex plate (mm)					
S.A.E.	BX	U	X	Y	AH
14	466.72	438.15	8	14	25.4
11 ½	352.42	333.38	8	11	39.6
10	314.32	295.28	8	11	53.8
8	263.52	244.48	6	11	62

Torsional analysis data



*VL13, VL14 = Ø 85 mm

Centre of gravity: Xr (mm), Rotor length: Lr (mm), Weight: M (kg), Moment of inertia: J (kgm²): (4J = MD²)																
Flex plate	S.A.E. 8				S.A.E. 10				S.A.E. 11 1/2				S.A.E. 14			
Type	Xr	Lr	M	J	Xr	Lr	M	J	Xr	Lr	M	J	Xr	Lr	M	J
LSA 44.3 S2	362	729	121	0.855	353	729	121	0.868	322	729	127	0.883	318	729	123	1.007
LSA 44.3 S3	362	729	121	0.855	353	729	121	0.868	322	729	127	0.883	318	729	123	1.007
LSA 44.3 S4	383	729	139	1.013	372	729	139	1.026	359	729	138	1.041	337	729	141	1.165
LSA 44.3 S5	383	729	139	1.013	372	729	139	1.026	359	729	138	1.041	337	729	141	1.165
LSA 44.3 M6	408	799	154	1.129	399	799	154	1.142	386	799	153	1.157	364	799	156	1.281
LSA 44.3 M8	418	799	165	1.236	410	799	165	1.249	397	799	165	1.264	373	799	168	1.388
LSA 44.3 L10	438	839	181	1.371	429	839	181	1.384	417	839	180	1.399	397	839	183	1.523
LSA 44.3 L12	437	839	181	1.381	428	839	181	1.394	416	839	181	1.409	396	839	184	1.533
LSA 44.3 VL13	473	922.4	224	1.739	465	914	224	1.753	451	899	224	1.769	436.5	906	231	1.899
LSA 44.3 VL14	473	922.4	224	1.739	465	914	224	1.753	451	899	224	1.769	436.5	906	231	1.899

NOTE : Dimensions are for information only and may be subject to modifications. Contractual 2D drawings can be downloaded from the Leroy-Somer site, 3D drawing files are available upon request.
The torsional analysis of the transmission is imperative. All values are available upon request.

Two bearing dimensions



Dimensions (mm) and weight						
Type	L without PMG	LB	Xg	C	H*	Weight (kg)
LSA 44.3 S2	807	702	333	260	270	301
LSA 44.3 S3	807	702	333	260	270	301
LSA 44.3 S4	807	702	350	260	270	338
LSA 44.3 S5	807	702	350	260	270	338
LSA 44.3 M6	877	772	373	260	270	374
LSA 44.3 M8	877	772	385	260	270	404
LSA 44.3 L10	917	812	403	260	270	439
LSA 44.3 L12	917	812	393	260	270	439
LSA 44.3 VL13	1002	897	422	285	270	555
LSA 44.3 VL14	1002	897	422	285	270	555

* H options: 225 mm, not available for VL13 and VL14, or 280 mm, available only for VL13 and VL14. Drawing available upon request.

Torsional analysis data



*VL13, VL14 = Ø 85 mm

Centre of gravity: Xr (mm), Rotor length: Lr (mm), Weight: M (kg), Moment of inertia: J (kgm²): (4J = MD²)				
Type	Xr	Lr	M	J
LSA 44.3 S2	309	793	117	0.825
LSA 44.3 S3	309	793	117	0.825
LSA 44.3 S4	329	793	135	0.988
LSA 44.3 S5	329	793	135	0.988
LSA 44.3 M6	353	863	149	1.096
LSA 44.3 M8	363	863	161	1.203
LSA 44.3 L10	383	903	176	1.346
LSA 44.3 L12	382	903	177	1.356
LSA 44.3 VL13	409	988	219.5	1.706
LSA 44.3 VL14	409	988	219.5	1.706

NOTE : Dimensions are for information only and may be subject to modifications. Contractual 2D drawings can be downloaded from the Leroy-Somer site, 3D drawing files are available upon request.
The torsional analysis of the transmission is imperative. All values are available upon request.

LEROY-SOMER™

www.leroy-somer.com/epg

Linkedin.com/company/leroy-somer
Twitter.com/Leroy_Somer_en
Facebook.com/LeroySomer.Nidec.en
YouTube.com/LeroySomerOfficiel

Nidec
All for dreams

© Nidec 2020. The information contained in this brochure is for guidance only and does not form part of any contract. The accuracy cannot be guaranteed as Nidec have an ongoing process of development and reserve the right to change the specification of their products without notice.

Moteurs Leroy-Somer SAS. Siège : Bd Marcellin Leroy, CS 10015, 16915 Angoulême Cedex 9, France. Capital social : 65 800 512 €, RCS Angoulême 338 567 258.

5028 en - 2020.03 / k